



REV.	ECR NO.	DATE	SIGN	DESCRIPTION
A		2010.12.14	曾志红	NEW DWG
B		2011.03.03	LEB	NEW DWG
C		2011.04.26	LEB	变更料号
D		2015.07.30	李震	增加图面序号以及重点管控尺寸

- 1.1: Housing: LCP UL94-V0 Color:Nature.
- 1.2: Contact: CS191-H T=0.20±0.01.
- 1.3: LEG: C2680-H T=0.25±0.01.

- 2.1: Contact: Gold flash over Nickel.
- 2.2: LEG: Gold flash over Nickel.

- 3.1: Operating Voltage: 50V AC/DC.
- 3.2: Current Rating: 0.5A AC/DC.
- 3.3: Operating Temperature: -40°C~+80°C.

- 4: Mark "△" is the important dimension
- 5: Part Number:

- FPC 05 11-XX R-TA x

- △ 0=Matte Sn Plating Over all;
- G=Gold Flash
- TA: Tape Reel Packing
- TU: Tube Packing
- RIGHT ANGLE(DOUBLE-FACE CONTACT)
- NO.OF CONTACTS
- SERIE NUMBER
- PITCH=0.5MM
- FPC SERIES

PORT NO	Dimension			PORT NO	Dimension		
	A	B	D		A	B	D
04P	4.10	3.25	2.60	25P	14.60	13.75	13.10
05P	4.60	3.75	3.10	26P	15.10	14.25	13.60
06P	5.10	4.25	3.60	27P	15.60	14.75	14.10
07P	5.60	4.75	4.10	28P	16.10	15.25	14.60
08P	6.10	5.25	4.60	29P	16.60	15.75	15.10
09P	6.60	5.75	5.10	30P	17.10	16.25	15.60
10P	7.10	6.25	5.60	31P	17.60	16.75	16.10
11P	7.60	6.75	6.10	32P	18.10	17.25	16.60
12P	8.10	7.25	6.60	33P	18.60	17.75	17.10
13P	8.60	7.75	7.10	34P	19.10	18.25	17.60
14P	9.10	8.25	7.60	35P	19.60	18.75	18.10
15P	9.60	8.75	8.10	36P	20.10	19.25	18.60
16P	10.10	9.25	8.60	37P	20.60	19.75	19.10
17P	10.60	9.75	9.10	38P	21.10	20.25	19.60
18P	11.10	10.25	9.60	39P	21.60	20.75	20.10
19P	11.60	10.75	10.10	40P	22.10	21.25	20.60
20P	12.10	11.25	10.60	41P	22.60	21.75	21.10
21P	12.60	11.75	11.10	42P	23.10	22.25	21.60
22P	13.10	12.25	11.60	43P	23.60	22.75	22.10
23P	13.60	12.75	12.10	44P	24.10	23.25	22.60
24P	14.10	13.25	12.60	45P	24.60	23.75	23.10

众鸣精密工业（深圳）有限公司

众鸣连接器

Tel: +86-13590178542

Email: kjzmlucy@aliyun.com

www.zmconnector.com

TOLERANCE UNLESS SPECIFIED	DATE	DAR. BY	MATERIAL
LINEAR	2011.04.26		
ANGLE		CHK. BY	FINISH
SCALE 1/1		APP. BY	DWG NO.
UNIT MM			